



Yamaha G14/16/19/22 Nerf Bars w/ Diamond Plate Inlays
Installation Instructions
Black- Part# 30866 Stainless Part# 28344

Hardware Kit

- 4- 1" Spacers
- 6- 1/4" lock nuts
- 8- 5/16" locknuts
- 6- 1/4" washers
- 8- 5/16" washers
- 6- 1/4 x 3/4 button heads
- 4- 5/16 x 2 1/2 button heads
- 4- 5/16 x 1 1/4 bolts



Always wear appropriate eye protection!

Installation Instructions:

1. Remove the plastic rocker covers from both sides of the cart.
2. Using the supplied 1/4 x 3/4 button heads, 1/4" washers, & 1/4" locknuts install the diamond plate rockers to the nerf bars.
3. Hold the nerf bars against the outside of the rockers. Using a punch mark one of the proposed mounting areas as shown in Figure 1. **NOTE: Before drilling, make sure hole locations do not interfere with the carts original gussets, brackets or accessory wiring on the backside of the rocker panels.**
4. Drill a 5/16" hole in the marked location as shown in Figure 2. Measure from the bottom of the rocker to the center of the drilled hole. Measure from center hole to center hole of the nerf bar mounts. Using these measurements mark and drill the 2nd hole for mounting the nerf bars.
5. Using the supplied 5/16 x 1 1/4 bolts, locknuts, spacer plate and support plate mount the support plate to the stock rocker support as shown in Figure 4.
6. Using the supplied 1/2" spacer, 5/16 x 2 1/2 button head bolts, 5/16 washers, & 5/16 locknuts mount the nerf bars to the back side of the stock rockers as shown in Figure 3.
7. Reinstall stock rocker covers.
8. Repeat steps 2-7 for the other side of the cart.

Figure 1



Figure 2



Figure 3



Figure 4

