



Yamaha G14/16/19/22 Nerf Bars Installation Instructions Black- Part# 29071 Stainless Part# 29096

Hardware Kit

- 4- 1" Spacers
- 4- 5/16" locknuts
- 8- 5/16" washers
- 4- 5/16 x 2 1/2 button heads



 *Always wear appropriate eye protection!*

Installation Instructions:

1. Remove the plastic rocker covers from both sides of the cart.
2. Hold the nerf bars against the outside of the rockers. Using a punch mark one of the proposed mounting areas as shown in Figure 1. **NOTE: Before drilling, make sure hole locations do not interfere with the carts original gussets, brackets or accessory wiring on the backside of the rocker panels.**
3. Drill a 5/16" hole in the marked location as shown in Figure 2. Measure from the bottom of the rocker to the center of the drilled hole. Measure from center hole to center hole of the nerf bar mounts. Using these measurements mark and drill the 2nd hole for mounting the nerf bars.
4. Using the supplied 1/2" spacer, 5/16 x 2 1/2 button head bolts, 5/16 washers, & 5/16 locknuts mount the nerf bars to the back side of the stock rockers as shown in Figure 3.
5. Reinstall stock rocker covers.
6. Repeat steps 2-6 for the other side of the cart.

